

# TECHNICAL SPECIFICATIONS

# RF 85mm F2 MACRO IS STM

## OPTICAL FEATURES/ SPECIFICATIONS

<b>Image size</b>	Full Frame
<b>Angle of view (horzntl, vertl, diagnl)</b>	24°, 16°, 28° 30'
<b>Lens construction (elements/groups)</b>	12/11
<b>No. of diaphragm blades</b>	9
<b>Minimum aperture</b>	29
<b>Closest focussing distance (m)</b>	0.35
<b>Maximum magnification (x)</b>	0.5
<b>Distance Information</b>	Yes
<b>Image stabilizer <sup>[2]</sup></b>	5
<b>AF actuator</b>	STM

## PHYSICAL SPECIFICATIONS

<b>Dust/moisture resistance <sup>[1]</sup></b>	No
<b>Filter diameter (mm)</b>	67
<b>Max. diameter x length (mm)</b>	78 x 90.5
<b>Weight (g)</b>	500

## ACCESSORIES

<b>Lens Cap</b>	E-67 II
<b>Lens hood</b>	ET-77
<b>Lens case/pouch</b>	LP-1216

### Footnotes

<sup>[1]</sup> Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

<sup>[2]</sup> Tested under CIPA standards



Canon Inc.  
canon.com  
Canon Europe  
canon-europe.com  
English edition  
Canon Europa NV 2020

---

Live for the story\_